

Technical Datasheet - Premium Paper Labels

Premium Paper Labels - Gloss White

Paper: White, woodfree machine coated gloss

Weight: 90gsm

Adhesive: Aqueous acrylic emulsion adhesive Minimum application temperature: +5°C Temperature range: -15°C to +80°C

Chill grade: Ideal for sandwich/chilled food labelling

ADHESIVE

Designed for laminates in a wide range of applications

Very good heat resistance which enables trouble free performance in different hot fusing print processes Good adhesion to cardboard and low energy (e.g., plastic bags) surfaces

Good 'all round' permanent adhesive

Approved for direct contact on dry and 'moist' non-fatty foods

The adhesive conforms to the EN71-3 (Toy Safety) & Packaging (Essential Requirements) Regulations No heavy metals are used in the manufacturing process and typical contents are less than 1ppm

BACKING

White high density kraft paper with excellent lay flat properties

Premium Paper Labels - Gloss White Removable

Paper: White, woodfree machine coated gloss

Weight: 90gsm

Adhesive: Aqueous acrylic emulsion removable adhesive

Minimum application temperature: +15°C

Temperature range: -5°C to +60°C

Adhesive: Approved for direct contact on dry and 'moist' non-fatty foods Backing: White high density kraft paper with excellent lay flat properties



Technical Datasheet - Premium Paper Labels

Premium Paper Labels - Matt White Recycled

Paper: Matt white, woodfree paper made from 100% Post Consumer Waste (PCW), bleached without chlorine

Weight: 80gsm

Adhesive: General purpose permanent, acrylic based adhesive

Minimum application temperature: 0°C Temperature range: -20°C to +80°C

Backing: A one side coared, bleached kraft paper

Weight: 80gsm

Conforms to the EN71-3 (Toy Safety) Regulations

No heavy metals are used in the manufacturing process

No animal derived materials used in the manufacture or the formulation of the product

No genetically modified organism (GMO) derived materials used in the manufacture or the formulation of the product

No substances or chemicals known to cause cancer or reproductive toxicity used in the manufacture or the formulation of the product

Premium Paper Labels - Brown Kraft Recycled

Paper: Brown kraft paper made from 100% Post Consumer Waste (PCW)

Weight: 85gsm

Adhesive: High tack permanent acrylic emulsion adhesive

Minimum application temperature: 0°C Temperature range: -50°C to +90°C

Backing: White high density kraft paper with excellent lay flat properties